



# UNITED STATES WELDING CORPORATION

<p align="center"><b>USW ALLOY DESIGNATION AND DESCRIPTION</b></p>	<p align="center"><b>TURBALOY<sup>®</sup> 91</b> MC-GRADE GTAW SOLID BARE WELDING WIRE IRON BASE</p>	<p align="center"><b>ISSUED</b> JANURAY 2007</p>	<p align="center"><b>DATA SHEET</b>  <b>1677</b> (1)</p>																																																						
<p align="center"><b>CROSS-REFERENCE CONFORMANCE SPECIFICATIONS</b></p>	<p>USW 1677 Modified 9Cr 1Mo AWS A5.28 ER90S-B9 9Cr 1Mo.V.Cb.N ER505 Modified</p> <p>Numerous company specifications with minor variations (see USW 1689 &amp; USW 1866) Trace elements controlled (TEC) (Non-copper coated) Available in HQ-GRADE</p>																																																								
<p align="center"><b>METALLURGICAL BACKGROUND INFORMATION</b></p>	<p>TURBALOY<sup>®</sup> 91 is produced by vacuum induction melting and remelting techniques. The final wire is manufactured by special lubricant-free, roller-die forming followed by surface abrasion and cleaning processes. These manufacturing processes ensure consistent metallurgical integrity of the alloy with regard to control of trace elements and physical purity of the welding wire surface.</p> <p>TURBALOY<sup>®</sup> 91 is a 9Cr 1Mo double stabilized, nitrogen strengthened filler metal having excellent creep properties and reproducible, sound X-ray quality welds in base materials of similar composition. Original alloy development was done at Oak Ridge Laboratories for TVA and CE Corp. Note the low manganese aim that is adopted.</p>																																																								
<p align="center"><b>MATERIALS TO BE WELDED AND APPLICATIONS</b></p>	<p>MC-GRADE TURBALOY<sup>®</sup> 91 is generally applied using GTAW. It is extensively used for steam turbine overhaul, repair and manufacture as well as for boiler tube and superheater tube fabrication and repair. The alloy is now well established and is in extensive use worldwide for power station applications - both nuclear and fossil fueled. Used on base alloys of 9Cr 1Mo and similar compositions.</p>																																																								
<p align="center"><b>WIRE CHEMISTRY WT%</b></p>	<table border="0"> <tr> <td>Carbon</td> <td>0.08</td> <td>0.11 (aim 0.10)</td> <td>Columbium</td> <td>0.04</td> <td>0.08</td> </tr> <tr> <td>Manganese</td> <td>0.40</td> <td>0.60 (aim 0.47)</td> <td>Oxygen</td> <td>-</td> <td>0.008 (80ppm)</td> </tr> <tr> <td>Silicon</td> <td>0.15</td> <td>0.30</td> <td>Nitrogen</td> <td>0.030</td> <td>0.050</td> </tr> <tr> <td>Sulfur</td> <td>-</td> <td>0.008</td> <td>Hydrogen</td> <td>-</td> <td>0.001 (10ppm)</td> </tr> <tr> <td>Phosphorus</td> <td>-</td> <td>0.010</td> <td>Boron</td> <td>-</td> <td>0.001 (10ppm)</td> </tr> <tr> <td>Chromium</td> <td>8.0</td> <td>9.50</td> <td>Aluminum</td> <td>-</td> <td>0.01</td> </tr> <tr> <td>Nickel</td> <td>-</td> <td>0.30</td> <td>Copper</td> <td>-</td> <td>0.10</td> </tr> <tr> <td>Molybdenum</td> <td>0.85</td> <td>1.05</td> <td>Iron</td> <td></td> <td>Balance</td> </tr> <tr> <td>Vanadium</td> <td>0.18</td> <td>0.25</td> <td></td> <td></td> <td></td> </tr> </table>			Carbon	0.08	0.11 (aim 0.10)	Columbium	0.04	0.08	Manganese	0.40	0.60 (aim 0.47)	Oxygen	-	0.008 (80ppm)	Silicon	0.15	0.30	Nitrogen	0.030	0.050	Sulfur	-	0.008	Hydrogen	-	0.001 (10ppm)	Phosphorus	-	0.010	Boron	-	0.001 (10ppm)	Chromium	8.0	9.50	Aluminum	-	0.01	Nickel	-	0.30	Copper	-	0.10	Molybdenum	0.85	1.05	Iron		Balance	Vanadium	0.18	0.25			
Carbon	0.08	0.11 (aim 0.10)	Columbium	0.04	0.08																																																				
Manganese	0.40	0.60 (aim 0.47)	Oxygen	-	0.008 (80ppm)																																																				
Silicon	0.15	0.30	Nitrogen	0.030	0.050																																																				
Sulfur	-	0.008	Hydrogen	-	0.001 (10ppm)																																																				
Phosphorus	-	0.010	Boron	-	0.001 (10ppm)																																																				
Chromium	8.0	9.50	Aluminum	-	0.01																																																				
Nickel	-	0.30	Copper	-	0.10																																																				
Molybdenum	0.85	1.05	Iron		Balance																																																				
Vanadium	0.18	0.25																																																							
<p align="center"><b>WELD PROPERTIES</b> after Normalized 1900°F Temper 1340°F (air cool)</p>	<table border="0"> <tr> <td>0.02% offset proof stress</td> <td>66.41 ksi</td> <td></td> <td></td> </tr> <tr> <td>0.20% offset yield strength</td> <td>76.46 ksi</td> <td>RA 70%</td> <td></td> </tr> <tr> <td>Ultimate tensile strength</td> <td>94.98 ksi</td> <td>Elongation 25%</td> <td></td> </tr> </table>			0.02% offset proof stress	66.41 ksi			0.20% offset yield strength	76.46 ksi	RA 70%		Ultimate tensile strength	94.98 ksi	Elongation 25%																																											
0.02% offset proof stress	66.41 ksi																																																								
0.20% offset yield strength	76.46 ksi	RA 70%																																																							
Ultimate tensile strength	94.98 ksi	Elongation 25%																																																							
<p align="center"><b>SIZES AND FORMS AVAILABLE</b></p>	<table border="0"> <tr> <td align="center" colspan="2">STRAIGHT LENGTHS</td> <td align="center" colspan="2">SPOOLED WIRE</td> </tr> <tr> <td>5 lb. (2.2kg) packs</td> <td></td> <td>Precision layer wound, with controlled cast and helix</td> <td></td> </tr> <tr> <td>36" (914mm) lengths</td> <td></td> <td>12" (300mm) diameter spools standard</td> <td></td> </tr> <tr> <td>Flag tagged for traceability.</td> <td></td> <td>8" (200mm), 4" (100mm) and proprietary spool sizes</td> <td></td> </tr> <tr> <td>(Double tagging and other lengths on request)</td> <td></td> <td>on request.</td> <td></td> </tr> <tr> <td>Wide range of diameters.</td> <td></td> <td>Wide range of diameters and spool weights.</td> <td></td> </tr> </table>			STRAIGHT LENGTHS		SPOOLED WIRE		5 lb. (2.2kg) packs		Precision layer wound, with controlled cast and helix		36" (914mm) lengths		12" (300mm) diameter spools standard		Flag tagged for traceability.		8" (200mm), 4" (100mm) and proprietary spool sizes		(Double tagging and other lengths on request)		on request.		Wide range of diameters.		Wide range of diameters and spool weights.																															
STRAIGHT LENGTHS		SPOOLED WIRE																																																							
5 lb. (2.2kg) packs		Precision layer wound, with controlled cast and helix																																																							
36" (914mm) lengths		12" (300mm) diameter spools standard																																																							
Flag tagged for traceability.		8" (200mm), 4" (100mm) and proprietary spool sizes																																																							
(Double tagging and other lengths on request)		on request.																																																							
Wide range of diameters.		Wide range of diameters and spool weights.																																																							
<p align="center"><b>PACKAGING</b></p>	<p>Sealed, air-evacuated, argon purged Vapor Barrier envelopes with desiccants ensure full protection from atmospheric contamination and prolonged shelf-life.</p>																																																								

DISTRIBUTED BY: