



# UNITED STATES WELDING CORPORATION

<p align="center"><b>USW ALLOY DESIGNATION AND DESCRIPTION</b></p>	<p align="center"><b>TURBALOY® 286VM</b> MC-GRADE <b>GTAW SOLID BARE WELDING WIRE</b> IRON BASE</p>	<p align="center"><b>ISSUED</b> JANUARY 2007</p>	<p align="center"><b>DATA SHEET</b>  <b>5805</b> (22)</p>																																																						
<p align="center"><b>CROSS-REFERENCE CONFORMANCE SPECIFICATIONS</b></p>	<table border="0"> <tr> <td>AMS 5805</td> <td>15Cr 25.5Ni 1.2Mo 2.1Ti 0.004B 0.30V</td> </tr> <tr> <td>MSRR 9500/234</td> <td>USWC 5805 (V)</td> </tr> <tr> <td>A286VM</td> <td>AISI 660</td> </tr> <tr> <td>UNS S66286</td> <td>Available in HQ-GRADE</td> </tr> <tr> <td>Tinidur</td> <td>(Note: AMS 5805 is used in preference to AMS 5804-9500/233)</td> </tr> </table>			AMS 5805	15Cr 25.5Ni 1.2Mo 2.1Ti 0.004B 0.30V	MSRR 9500/234	USWC 5805 (V)	A286VM	AISI 660	UNS S66286	Available in HQ-GRADE	Tinidur	(Note: AMS 5805 is used in preference to AMS 5804-9500/233)																																												
AMS 5805	15Cr 25.5Ni 1.2Mo 2.1Ti 0.004B 0.30V																																																								
MSRR 9500/234	USWC 5805 (V)																																																								
A286VM	AISI 660																																																								
UNS S66286	Available in HQ-GRADE																																																								
Tinidur	(Note: AMS 5805 is used in preference to AMS 5804-9500/233)																																																								
<p align="center"><b>METALLURGICAL BACKGROUND INFORMATION</b></p>	<p>TURBALOY® 286VM is produced by vacuum induction melting and remelting techniques. The final wire is manufactured by special lubricant-free, roller-die forming followed by surface abrasion and cleaning processes.</p> <p>These manufacturing processes ensure consistent metallurgical integrity of the alloy with regard to control of trace elements and physical purity of the welding wire surface.</p> <p>TURBALOY® 286 VM is a precipitation hardening, austenitic stainless alloy used for high temperature strength and oxidation resistance. It is used to weld A286 base alloy on numerous turbine components including after-burners, turbine cases, wheels and blades, framework.</p>																																																								
<p align="center"><b>MATERIALS TO BE WELDED AND APPLICATIONS</b></p>	<p>AMS 5525, 5726, 5731, 5732, 5734, 5735, 5736, 5737, 5858, 5895. GE B50T12, B50T81, B50T1181, AISI 660. ASTM A638, PWA 1075, PWA 1092.</p> <p>Best results will be obtained when welding A286 in the solution treated condition. Ultra clean conditions and MC-GRADE wire help to reduce susceptibility to hot-crack formation.</p>																																																								
<p align="center"><b>WIRE CHEMISTRY WT%</b></p>	<table border="0"> <tr> <td>Carbon</td> <td>-</td> <td>0.04</td> <td>Cobalt</td> <td>-</td> <td>1.00</td> </tr> <tr> <td>Manganese</td> <td>-</td> <td>0.35</td> <td>Titanium</td> <td>1.90</td> <td>2.30</td> </tr> <tr> <td>Silicon</td> <td>-</td> <td>0.25</td> <td>Boron</td> <td>0.003</td> <td>0.005</td> </tr> <tr> <td>Sulfur</td> <td>-</td> <td>0.005</td> <td>Vanadium</td> <td>0.10</td> <td>0.50</td> </tr> <tr> <td>Phosphorus</td> <td>-</td> <td>0.01</td> <td>Aluminum</td> <td>-</td> <td>0.35</td> </tr> <tr> <td>Chromium</td> <td>13.50</td> <td>16.00</td> <td>Oxygen</td> <td>-</td> <td>0.005 (50ppm)</td> </tr> <tr> <td>Nickel</td> <td>24.00</td> <td>27.00</td> <td>Nitrogen</td> <td>-</td> <td>0.005 (50ppm)</td> </tr> <tr> <td>Molybdenum</td> <td>1.00</td> <td>1.50</td> <td>Hydrogen</td> <td>-</td> <td>0.0005 (5ppm)</td> </tr> <tr> <td></td> <td></td> <td></td> <td>Iron</td> <td></td> <td>Balance</td> </tr> </table>			Carbon	-	0.04	Cobalt	-	1.00	Manganese	-	0.35	Titanium	1.90	2.30	Silicon	-	0.25	Boron	0.003	0.005	Sulfur	-	0.005	Vanadium	0.10	0.50	Phosphorus	-	0.01	Aluminum	-	0.35	Chromium	13.50	16.00	Oxygen	-	0.005 (50ppm)	Nickel	24.00	27.00	Nitrogen	-	0.005 (50ppm)	Molybdenum	1.00	1.50	Hydrogen	-	0.0005 (5ppm)				Iron		Balance
Carbon	-	0.04	Cobalt	-	1.00																																																				
Manganese	-	0.35	Titanium	1.90	2.30																																																				
Silicon	-	0.25	Boron	0.003	0.005																																																				
Sulfur	-	0.005	Vanadium	0.10	0.50																																																				
Phosphorus	-	0.01	Aluminum	-	0.35																																																				
Chromium	13.50	16.00	Oxygen	-	0.005 (50ppm)																																																				
Nickel	24.00	27.00	Nitrogen	-	0.005 (50ppm)																																																				
Molybdenum	1.00	1.50	Hydrogen	-	0.0005 (5ppm)																																																				
			Iron		Balance																																																				
<p align="center"><b>WELD PROPERTIES</b></p>	<p>Melting range: 2500°F - 2600°F Hardness: aged 28 HRC</p> <p align="right">Density: 7.9 gm/cc</p>																																																								
<p align="center"><b>SIZES AND FORMS AVAILABLE</b></p>	<table border="0"> <tr> <td align="center" colspan="2">STRAIGHT LENGTHS</td> <td align="center" colspan="2">SPOOLED WIRE</td> </tr> <tr> <td>5 lb. (2.2kg) packs</td> <td></td> <td>Precision layer wound, with controlled cast and helix</td> <td></td> </tr> <tr> <td>36" (914mm) lengths</td> <td></td> <td>12" (300mm) diameter spools standard</td> <td></td> </tr> <tr> <td>Flag tagged for traceability.</td> <td></td> <td>8" (200mm), 4" (100mm) and proprietary spool sizes</td> <td></td> </tr> <tr> <td>(Double tagging and other lengths on request)</td> <td></td> <td>on request.</td> <td></td> </tr> <tr> <td>Wide range of diameters.</td> <td></td> <td>Wide range of diameters and spool weights.</td> <td></td> </tr> </table>			STRAIGHT LENGTHS		SPOOLED WIRE		5 lb. (2.2kg) packs		Precision layer wound, with controlled cast and helix		36" (914mm) lengths		12" (300mm) diameter spools standard		Flag tagged for traceability.		8" (200mm), 4" (100mm) and proprietary spool sizes		(Double tagging and other lengths on request)		on request.		Wide range of diameters.		Wide range of diameters and spool weights.																															
STRAIGHT LENGTHS		SPOOLED WIRE																																																							
5 lb. (2.2kg) packs		Precision layer wound, with controlled cast and helix																																																							
36" (914mm) lengths		12" (300mm) diameter spools standard																																																							
Flag tagged for traceability.		8" (200mm), 4" (100mm) and proprietary spool sizes																																																							
(Double tagging and other lengths on request)		on request.																																																							
Wide range of diameters.		Wide range of diameters and spool weights.																																																							
<p align="center"><b>PACKAGING</b></p>	<p>Sealed polyethylene envelopes. (Desiccants optional)</p>																																																								

DISTRIBUTED BY: